



Ledge Access Panel Product Data

Manufacturer

GC Products, Inc.
1601 Aviation Blvd, Suite 150
Lincoln, CA 95648
P 916.645.3870 F 916.645.3857
www.gcproductsinc.com

Standard Sizes

Ledge GFRG Access Panels are generally specified by their opening sizes. Typically, an additional 6" needs to be added for the rough opening size (see installation detail for clarification).

All standard access panel sizes are available with drop-in or hinged type doors. Panels are gypsum based for interior applications (cement-based panels are available for exterior use and may be special ordered). Custom sizes are available upon request. Please contact GC Products or visit www.LedgePanels.com for more information.

Standard Door (Opening) Sizes

9" x 9"	(4 lbs.)	24" x 24"	(12 lbs.)
12" x 12"	(6 lbs.)	22 ½" x 30"	(15 lbs.)
16" x 16"	(8 lbs.)	30" x 30"	(19 lbs.)
18" x 18"	(9 lbs.)		

Fastener & Attachments (by installer)

Access panels are installed with #6 bugle head screws, joint at perimeter of rough opening is concealed via tape joint. Fill, sand and finish as required.

Finishing

All finishing is done by installer.

Framing

Framing is determined by the job-site conditions. The panel does not require regular framing but can be connected to adjacent drywall using blocks or studs.

Physical Specifications

• Shell Thickness	1/8" to 3/16"
• Fastener Test Pull Out (wood stud)	525 lbs. Avg.
• Fastener Test Pull Out (metal stud)	215 lbs. Avg.
• Fastener Push Through Test	350 lbs. Avg.
• Flame Spread (ASTM E84)	0
• Smoke Index (ASTM E84)	5
• Combustion (ASTM E84)	None
• Classification (ASTM E84)	A
• Fire Rating	Non-Rated

Environmental Testing

Ledge GFRG Access Panels meet the Volatile Organic Compound (VOC) emissions requirements according to the California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017 (Emission testing method for CA Specification 01350)